



C-GM/5BM

15-pin HD to 5 BNC Breakout Cables



Kramer's computer graphics video breakout cables are constructed of 5 mini coax cables with a molded 15-pin HD (M or F) on one end and 5 BNC (M or F) on the other. They convert between the two most common cabling formats used for routing computer graphic video signals, 15-pin HD, and 5 BNC.

FEATURES

- **Quality Construction** - Constructed using Kramer BC-5X high resolution mini coax cable, terminated with molded 15-pin HD connector on one end and 75Ω BNC connectors on the other.
- **Easy Installation** - Models 6ft or longer have an 18in (460mm) long spread at the 5 BNC end to fit large routers/switchers such as the Sierra Pro 32 series.
- **Cable Specs** - See Kramer BC-5X for detailed cable specs.
- **Varied Selection of Lengths** - 0.5 to 100ft (0.2 to 30.5m).

Model	Description	Length Meter	
Male - Male			
C-GM/5BM-1	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	1'	0.3M
C-GM/5BM-3	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	3'	0.9M
C-GM/5BM-6	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	6'	1.8M
C-GM/5BM-10	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	10'	3.0M
C-GM/5BM-15	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	15'	4.6M
C-GM/5BM-25	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	25'	7.6M
C-GM/5BM-50	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	50'	15.2M
C-GM/5BM-75	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	75'	22.9M
C-GM/5BM-100	Molded 15-pin HD (M) to 5 BNC (M) Breakout Cable	100'	30.5M