

ACT-50H Handheld Transmitter

Key Features

- Rugged, ergonomically designed metal housing.
- Unique sturdy multi-layered steel grilles not only protect the capsule against impact, anti-roll and pop noise, but also ensure transparent sound clarity.
- Interchangeable capsule module with premium condenser or dynamic options for easy and fast changeovers.
- Proprietary true condenser capsule exhibits high fidelity, wide dynamic range, fast transient responses, good feedback rejection, accurate sound image characteristics, transparent sound quality, and withstands maximum SPL.
- Proprietary dynamic capsule exhibits low handling & impact noise characteristics.
- Proprietary lockable silent on/off switch to avoid accidental power-off during performance.
- Patented, integrated grille and battery housing design enable fast and easy 2 AA battery installation and replacement.
- Impact-resistant battery compartment holds 2 AA batteries with color-coded rings for easy channel identification on stage.
- LCD displays working channel, battery status indicator, and error code messages
- Low spurious PLL-synthesized technology enhances frequency stability and reliability.
- One-touch ACT syncs the transmitter and receiver frequency automatically.
- Maximum 140dB SPL is achieved by the proprietary high dynamic range modulation circuitry.



Microphone Capsules


MU-39	Supercardioid Dynamic Capsule
MU-59	Supercardioid Dynamic Capsule
MU-70	Supercardioid Condenser Capsule
MU-80	Supercardioid Condenser Capsule
MU-90	Supercardioid Condenser Capsule

Accessories

MS-20	Desktop Microphone Tripod
MD-20	Handheld Transmitter Microphone Holder
RH-77a	Multi-colored ID rings

Technical Specifications

Housing	Metal
Oscillation Mode	PLL Synthesized
Frequency Range	UHF 480~934MHz
Bandwidth	24MHz
Channel Set-Up	ACT Sync
RF Output Power	10~30mW (country dependent)
Spurious Emissions	<-55dBc
Max. Input Level	140dB SPL
Display	LCD displays group, channel, battery status & error codes
Battery	2 AA alkaline
Battery Hours	Up to 16 hours (pending battery quality)
Dimensions	50(Ø)× 253(L)mm 2.0(Ø)×10(L)"
Weight	Approx. 301g 10.6oz (excluding batteries)



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw

Specifications subject to change without notice. SS015/06