

MM-70 Condenser Vocal Microphone

Introduction

The MM-70 is fitted with a MU-70 premium interchangeable cardioid condenser capsule module. Ideal for singing and public addressing.

Key Features

- Wider angle and feedback suppression.
- Sustains high SPL without distortion.
- The rugged grille protects the capsule against impact.
- Ultra-low handling and impact noise.

Technical Specifications

Capsule	MU-70
Housing	Die-cast zinc alloy
Polar Pattern	Cardioid
Sensitivity	-46 ± 1 dBV / Pa (0 dB=1V Open-circuit voltage), switchable gain setting of -6 dB on the capsule.
Frequency Response	50 Hz – 20 kHz (94 dB SPL)
Self-Noise	< 17 dB SPL (A-weighted)
S/N Ratio	> 78 dB @ 94 dB SPL (1 Pa)
Max. Input SPL	149 dB (Typical)
Dynamic Range	132 dB
Power Supply	External phantom power 12 – 52 V DC
Current Consumption	2.0 mA
Output Impedance	200 Ω
Dimensions (Ø × L)	51 × 200 mm 2 × 7.9 "
Weight	Approx. 225 g 8 oz



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw