



## NAC3FXXB-W-L

Locking AC mains cable connector, keyed and color coded (grey) for power-out, screw terminal assembly, for cable diameters 10 - 16 mm.

The powerCON FXXA/FXXB is a single phase (3 conductor) lockable power connector with Circuit Breaking Capability when mated with powerCON XX Series receptacles.

It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed to guarantee a safe power connection.



## Features & Benefits

- IEC EN 60320-1 / UL 60320-1 / CSA C22.2 No. 60320-1 certified, thus accepted as a component for cord sets acc. to IEC 60799 / UL 817 and equipment acc. to IEC 62368-1
- Ergonomic design with slip-proof two-component molded housing
- Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating
- Unique NEUTRIK locking bushing and strain relief for cable diameters 10 mm to 16 mm
- Easy to assemble because the strain relief locks with the insert mechanically and aligns with the housing
- Superior NEUTRIK quality standard, extremely robust and reliable
- Easy and reliable twist lock system
- Improved kink protection by two-component bushing

## Cable list

Cable: IEC/EN 60320-1			
	3 x 1.5 mm <sup>2</sup>	3 x 2.5 mm <sup>2</sup>	
■ H07RN-F	-S	-L	
■ H05RN-F	-S	-	
■ H05VV-F	-S	-S	
Cable: UL 60320-1, CAN/CSA-C22.2 No. 60320-1			
	16/3 AWG	14/3 AWG	12/3 AWG
■ SOOW	-S	-L	-L
■ SJOOW	-S	-S	-L
■ SJTOOW	-S	-S	-S

## Technical Information

### Produkte

Title	NAC3FXXB-W-L
Connector series	powerCON blue/grey

### Elektrisch

Contact resistance	$\leq 2 \text{ m}\Omega$
Dielectric strength	> 3 kVac (after mating cycles)
Insulation resistance	> 10 G $\Omega$ (initially)
Number of electrical contacts	2 + PE
Rating Europe	EN 60320-1: 16 A 250 V AC, CBC
Rating USA / Canada	cUL 60320-1: 20 A 127 V AC, CBC

### Mechanische Daten

Cable O.D.	10 – 16mm
Lifetime	Typically 5'000 mating cycles
Wiresize (mm <sup>2</sup> )	1.5 – 2.5 mm <sup>2</sup>
Wiresize (AWG)	14 – 12 AWG
Locking device	Twist lock
Termination	Screw type terminals

### Material

Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

**Umwelt**

<b>Temperature range</b>	-33 °C to + 80 °C
<b>Protection class</b>	IP20
<b>Flammability acc. to UL94</b>	V-0