

VS-211H2

2x1 4K60 4:4:4 HDCP 2.2 HDMI 2.0 Automatic Standby Switcher | HDMI | HDCP Compliant | 4K/60 UHD (4:2:0) | 4K/60 UHD (4:4:4)



The VS211H2 is a highperformance automatic switcher for 4K@60Hz (4:4:4) HDCP 2.2 HDMI 2.0 video signals. Offering priority and lastconnected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

FEATURES

Max. Data Rate - 17.82Gbps (5.94Gbps per data channel) Resolution Support - Up to 4K@60Hz (4:4:4) Kramer Equalization and re-Klocking Technology HDTV Compatible HDMI & HDCP 2.2 Compliant 3D Pass-Though



TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors
OUTPUTS:	1 HDMI connector
MAX. DATA RATE:	17.82GBPS (5.94Gbps per graphic channel)
MAX. RESOLUTION	4K@60 UHD (4:4:4)
COMPLIANCE WITH HDMI STANDARD:	HDCP and HDMI
CONTROLS:	Status/priority DIPswitches, contact closure remote control
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
POWER CONSUMPTION:	5V DC, 400mA
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.6kg (1.4lbs) approx
INCLUDED ACCESSORIES:	Power supply 5.2V DC/4A desktop
OPTIONS:	RK3T 19" rack adapter

